

Item Number	Size	Pattern	Tread Depth	32nds	Load Index	Speed Rating	Std. Rim	Section Width		Overall Dia.		Max. Load	Max. Load	Max. Air Pressure	Max. Air Pressure	Static Loaded Radius	Static Loaded Radius	Theoretical Rolling Radius	M+S	UTQG
			(mm)					(mm)	inch	(mm)	inch	(kg)	lbs (S)	(kPa)	psi	(mm)	(inch)			
LXS0960010II	245/35ZR20	LX-SIX II	8.00	10.00	95/XL	W	8½J	248	9.76	680	26.77	690	1521.16	290/340	42/49	321.08	12.64	330.09	M+S	420AA
LXS0960060II	245/40R20	LX-SIX II	8.00	10.00	99/XL	W	8½J	248	9.76	704	27.72	775	1708.55	290/340	42/49	324.85	12.79	341.74	M+S	420AA
LXS0960020II	255/35ZR20	LX-SIX II	8.00	10.00	97/XL	W	9J	260	10.24	686	27.01	730	1609.35	290/340	42/49	323.42	12.73	333.00	M+S	420AA
LXS0960030II	275/30ZR20	LX-SIX II	8.00	10.00	97/XL	W	9½J	278	10.94	674	26.54	730	1609.35	290/340	42/49	318.74	12.55	327.17	M+S	420AA
LXS0960070II	275/35R20	LX-SIX II	8.00	10.00	102/XL	W	9½J	278	10.94	700	27.56	850	1873.90	290/340	42/49	273.00	10.75	339.80	M+S	420AA
LXS0960050II	285/30ZR20	LX-SIX II	8.80	11.00	99/XL	W	10J	290	11.42	680	26.77	775	1708.55	290/340	42/49	321.08	12.64	330.09	M+S	420AA