

Item Number	Size	Pattern	Tread Depth	32nds	Load Index	Speed Rating	Std. Rim	Section Width		Overall Dia.		Max. Load	Max. Load	Max. Air Pressure	Max. Air Pressure	Static Loaded Radius	Static Loaded Radius	Theoretical Rolling Radius	M+S	UTQG
			(mm)					(mm)	inch	(mm)	inch									
LXSMB16010	LT265/75R16	MUD BEAST MT	12.30	15.50	123/120	Q	7½J	267	10.51	804	31.65	1550/1400	3415.00	550.00	79.77	372.18	14.65	407.80	M+S	420AA
LXSMB17010	LT295/70R17	MUD BEAST MT	14.80	18.50	121/118	Q	8½J	299	11.77	852	33.54	1320/1450	2910.00	550.00	79.77	394.49	15.53	384.82	M+S	420AA
LXSMB17020	35x12.50R17LT	MUD BEAST MT	16.30	20.50	121.00	Q	10J	318	12.52	883	34.76	1450	3195.00	450.00	65.26	407.66	16.05	371.31	M+S	420AA
LXSMB18020	33x12.50R18LT	MUD BEAST MT	16.30	20.50	118.00	Q	10J	318	12.52	826	32.52	1320	2910.00	450.00	65.26	385.34	15.17	396.94	M+S	420AA
LXSMB18010	35x12.50R18LT	MUD BEAST MT	16.30	20.50	118.00	Q	10J	318	12.52	883	34.76	1320	2910.00	350.00	50.04	409.57	16.12	371.31	M+S	420AA
LXSMB20010	33x12.50R20LT	MUD BEAST MT	16.30	20.50	114.00	Q	10J	318	12.52	832	32.76	1180	2600.00	450.00	65.26	391.70	15.42	394.07	M+S	420AA
LXSMB20020	35x12.50R20LT	MUD BEAST MT	16.30	20.50	121.00	Q	10J	318	12.52	883	34.76	1450	3195.00	450.00	65.26	413.38	16.27	371.31	M+S	420AA